

900 TREADMILL

The C900 Treadmill combines TRUE's newest technology and performance advancements with the dependable quality and low cost of ownership your facility demands. Backed by TRUE'S premium warranty, the C900 provides runners a high-end experience with the largest running surface in the industry, a speed range up to 17 mph, and TRUE's low-impact Soft System® and HRC Heart Rate Control®. Multiple console options provide customizable features, technology, and asset management capabilities for enhanced user engagement.

FEATURES

- Largest Running Surface in the Industry
- 17.0 MPH (27 KPH) Max speed with 18% Max incline
- HRC Cruise Control® and Soft System® deck
- Reversible / Waxed Deck

SPECIFICATIONS

DIMENSIONS (L X W X H)

84" x 34.5" x 60.5" / 213.36 cm x 87.63 cm x 153.67 cm

SPEED

0.5 to 17.0 MPH / 0.8 to 27 KPH

INCLINE/DECLINE LEVELS

0% to 18% (-3% to 18% with Decline Kit)

PRODUCT WEIGHT

450 lbs / 204 kg

COLOR

Charcoal/Black

CONSOLE OPTIONS











LED Console

Largest Running Surface in the Industry 62" L x 23" W / 157.4 cm x 58.4 cm



TRUE

ENVISION II 16" Touchscreen

ENVISION II 9" Touchscreen

SHOWRUNNER II 16" Integrated LCD

EMERGE II LED Console **IGNITE II**

900 SERIES



C900 TREADMILL

| JOOD INCLADIVILL | | |
|-----------------------------|--------------------------------|--|
| TECHNICAL SPECIFICATIONS | Power Source | 120V/20A (NEMA 5-20R receptacle) 230V/15A |
| | Cord Length | 12' / 3.7 M |
| | Drive Motor | 5 HP AC Self-Cooling Max Drive |
| | Motor Controller | PFC |
| | Incline Motor | 1,200 lbs. of thrust |
| | Speed Sensor | Optical |
| | Deck | Reversible / Waxed |
| | Belt | Maintenance Free |
| | Rollers | 3" / 8 cm w/ Shielded Bearings |
| | Impact System | True Soft System® |
| | Frame Construction | Robotically Welded Heavy-Gauge Steel |
| | Lubrication | None |
| | Speed Range | 0.5 to 17.0 MPH / 0.8 to 27 KPH |
| | Incline/Decline Range | 0% to 18% (-3% to 18% with Decline) |
| | Quick Access Control | Speed and Incline on Hand Grips with Start and Stop on Quick Access Point |
| | Handrail Design | Extended Handrails with Molded Rubber, Moisture-Resistant Grips |
| | Contact Heart Rate Monitoring | Yes |
| | Wireless Heart Rate Monitoring | Polar® Compatible |
| AVAILABLE CONSOLES | | Envision II 16", Envision II 9", ShowRunner II, Emerge II, Ignite II |
| ASSET TRACKING | | EcoFit Compatible |
| SAFETY | Safety Clip | Standard/Non-Removable |
| | Extended Handrails | Standard |
| | Large Straddle Covers | Standard |
| | User Detection | Person Present Detection |
| REGULATORY APPROVALS | | ETL UL1647, CSA, CE, EN957, (ISO 20957), FCC |
| EXTRAS | Accessories | Water Bottle Holder (2), Accessory Tray, Over Molded Reading Rack/Tablet Holder, Power Cord Management, Optional Medical Rails, Optional Decline Feet Kit |
| PHYSICAL SPECIFICATIONS | Footprint | 84" L x 34.5" W x 60.5" H / 213.36 cm x 87.63 cm x 153.67 cm |
| | Footprint with Decline | 84" L x 34.5" W x 62.5" H / 213.36 cm x 87.63 cm x 158.75 cm |
| | Running Surface | 62" L x 23" W / 157.4 cm x 58.4 cm |
| | Machine Weight | 450 lbs / 204 kg |
| | Shipping Weight | 489 lbs / 222.8 kg |
| | Maximum User Weight | 500 lbs / 226.7 kg |
| | Step-Up Height | 7" / 17.7 cm (9" / 22.86 cm with Optional Decline) |
| | Portability | 2 Front Transport Wheels |
| WARRANTY | Warranty Type | Commercial (all dues paying facilities, regardless of usage) |
| | Frame | Lifetime |
| | Motor | 5 Years |
| | Parts | 3 Years |
| | Labor | 3 Years |

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.

